

ROTARY TYPE AUTO PACKING MACHINE

-AR-60P-2-LQ -AR-60P-MASK





ROTARY TYPE AUTO PACKING MACHINE AR-60P



● 특징 / Feature

- 로타리식 자동급대 포장기는 분말, 과립, 고형물, 액상, 반고체 등의 충전포장물을 마음대로 선택하여 사용하실수 있습니다.
- 포장지가 정상적으로 공급되지 않을 경우 검출장치에 의해 충전 및 씰링을 하지 않으므로 봉지의 낭비를 줄입니다.
- AR-60P 로타리포장기는 8등분과 10등분으로 되어 있으며 봉지를 물고 있는 집게에 의해 정확하고 미려하게 씰링을 하여 줍니다.
- 제품의 모든 부품은 규격화되어 부품교체가 용이하여 편리하게 사용할 수 있습니다.
- 내용물 청소시 호퍼와 호스의 탈착이 가능하므로 세척이 용이하도록 세니타리식으로 되어 있습니다.
- AR-60P rotary-type automatic packing machine can be used by selecting the products in forms
 of powder, granule, solid substance, liquid type, semi-solid substance and etc. which are filled
 to be packed as you want.
- In case the packing paper is not normally supplied, the process of filling and sealing is stopped by the detection device so that the waste of the paper can be decreased.
- AR-60P rotary packing machine is composed of 8 and 10 equally-divided sections, and the tongs
 - that hold the paper makes the sealing exact and beautiful.
- As all component parts of this product is regulated, you can use them conveniently when the component part need to be exchanged.
- This is the sanitary type which makes it possible for the hopper and hose to be equipped and unequipped so that the washing job can be easy.



ROTARY TYPE AUTO PACKING MACHINE

AR-60P-2-LQ



● 사양 / Specification

MODEL	AR-60P-2-LQ	MODEL	AR-60P-2-LQ
포장열수	2열	PACKING LINE	2Lanes
생산능력	80pack/min	CAPACITY	80pack/min
포장규격	W80~120 X L100~200m/m	PACKING SIZE	W80~120 X L100~200m/m
충진용량	50~200ml	FILLING CAPACITY	50~200ml
포장형태	스텐딩파우치	PACKING TYPE	Standing bag
소비전력	약 5~8kw/hr	POWER CONSUMP	about 5∼8kw/hr
사용공압	5~6kg/cm	PNEUMATIC POWER	5~6kg/cm
사용전력	2.2kw, 220/380V (50~60hz)	ELECTRIC POWER	2.2kw, 220/380V (50~60hz)
기계중량	약 1,500kg	WEIGHT	about 1,500kg



ROTARY TYPE AUTO PACKING MACHINE

AR-60P-MASK



● 사양 / Specification

MODEL	AR-60P-MASK	MODEL	AR-60P-MASK
포장열수	2열	PACKING LINE	2Lanes
생산능력	30~60pack/min	CAPACITY	30∼60pack/min
포장규격	W80~150 X L100~250m/m	PACKING SIZE	W80∼150 X L100∼250m/m
충진용량	Sample	FILLING CAPACITY	Sample
포장형태	일반파우치	PACKING TYPE	General bag
소비전력	약 5~8kw/hr	POWER CONSUMP	about 5∼8kw/hr
사용공압	5~6kg/cm	PNEUMATIC POWER	5~6kg/cm
사용전력	2.2kw, 220/380V (50~60hz)	ELECTRIC POWER	2,2kw, 220/380V (50~60hz)
기계중량	약 1,500kg	WEIGHT	about 1,500kg

ROTARY TYPE AUTO PACKING MACHINE

AR-60P-2-LQ

- 액체커피
- 액체샴푸
- 페이스트 식품
- 장유
- 액체음료
- 기타 액체류
- Liquid coffee
- Liquid shampoo
- Paste type food
- Condiments
- Liquid drink
- Other liquids





AR-60P-MASK

- 마스크 씨트
- 각종고형물
- Mask sheet
- Other solid matter

● 포장내용물 / Contents

- ●조미료, 소금, 각종분말, 입자, 고형물, 액체,점도체, 제약품, 캔디, 제과, 물비누, 각종세제, 레토르트 식품, 마스크씨트, 액체커피
- Seasoning, Salt, Various kinds of powder, Particle, Solid substance, Liquid, Cohesive substance,
 Pharmaceutical product, Candy, Confectionary, Liquid soap, Various kinds of detergent and Retort food,
 Mask sheet, Liquid coffee

● 포장재료 / Packing Material

- ●NY+PE, OPP+PE, AL+PE, CP+PE, PAPER+PE, 기타 열접착 가능한 포장지
- ●NY+PE, OPP+PE, AL+PE, CP+PE, PAPER+PE and the other heat sealable materials

ROTARY TYPE AUTO PACKING MACHINE



본사 & 공장: 경기 고양시 일산동구 장항동 591-20 TEL: 031)908-9661~2 FAX: 031)908-9663

Head Office & Factory: 591-20 Janghang-dong, Ilsandong-gu, Koyang-si, Kyunggi-do, Korea

TEL: +82-31-908-9661~2 FAX: +82-31-908-9663

URL: http://www.autopackorea.com E-mail: autopack@korea.com